

NOZZLE FOR A GAS-INSULATED SWITCHING DEVICE AND RELATED
SWITCHING DEVICE

iAP20 Rec'd PCT/PTO 14 JUN 2006

DESCRIPTION

The present invention relates to a nozzle for a gas-insulated switching device for high- or
5 medium-voltage applications, i.e. for voltages above 1000 Volt, and to a related switching
device comprising such a nozzle.

As it is widely known in the art, gas insulated switching devices for high- and medium-
voltage applications normally comprise a fixed arc contact and a mobile arc contact; it is also
known that several types of gas switching devices for high- and medium-voltage applications
10 may additionally have a so-called fixed main or permanent contact and a corresponding
mobile main or permanent contact through which the current mainly passes when the gas
switching device is in a closed position.

In both solutions, during opening/closing operations, usually electric arcs strike between the
arcing contacts; a nozzle assembly is generally positioned around the arc contacts in order to
15 delimit the arcing zone and to restrain the potentially negative effects of such electric arcs. By
means of the nozzle assembly, a sufficient flow of gas is obtained in the arcing zone so as to
cool the arcing contacts sufficiently and remove heat; thus, circuit breaking is enabled to be
performed over the entire required interruption window and for currents going up to the short-
circuit breaking capacity.

20 Examples of existing nozzles are disclosed in patent documents US 6,483,064, US 5,216,214
and EP 0524088.

At present, known nozzle assemblies have some drawbacks, as regard in particular to their
constructive structure, manufacturing, and mounting in switching devices as well.

Indeed, known nozzle assemblies are generally realized by means of several different pieces,
25 mainly a converging-diverging body, made of insulating material, a so-called puffer cap, and

other additional components for realizing the mechanical connections. In particular, the insulating body is generally realized by using a cylinder of raw material which is machined, e.g. with a lathe, so as to obtain the desired shape; alternatively, the raw material is first preformed, thus achieving a rough shape, and then machined with suitable tools. In both cases a lot of raw materials is wasted and machining is usually difficult and time consuming.

Hence, costs and manufacturing time are not optimized, whilst assembly inside the switching device, due to the use of different pieces, is rather cumbersome and mechanically complicated. In particular, when the main contacts are present, the nozzle assembly is mounted by means of mechanical connection means on the mobile equipment of the main mobile contact, as described; for example in patent US 5,939,692; in addition to being more complicated, this solution is clearly not suitable when the switching device has only the arc contacts, thus forcing to adopt different constructive solutions and lacking in flexibility.

Finally, gas switching devices for high- and medium-voltage applications may further comprise an electrically conductive shield, positioned externally to and operatively associated with the nozzle assembly, in order to optimize the electric field distribution in the arcing zone and in its surroundings. Therefore, also this function is usually performed by means of an additional dedicated component and results in a non-optimized space occupation inside the device.

Alternatively, when the main contacts are present, the mobile main contact is machined so as it has a shape which performs the shielding function; in this case, particular care must be taken when shaping the contacts and assembling them on the structure of the switching device in order to avoid damages. This clearly results in a strong complication in the machinery of the mobile main contact and in assembling the switching device, with a consequent increase in manufacturing time and cost.

The main aim of the present invention is to provide a nozzle for a gas-switching device for

high- or medium-voltage applications, which allows to overcome the above mentioned drawbacks, and in particular which has an optimized structure and can be realized by a simplified manner with respect to known nozzles.

Within the scope of this aim, an object of the present invention is to provide a nozzle for a
5 gas-switching device for high- or medium-voltage applications, which is able to perform different operating functions with a reduced number of mechanical parts.

Another object of the present invention is to provide a nozzle for a gas-switching device for high- or medium-voltage applications, which allows easing its mounting inside the switching device.

10 A further object of the present invention is to provide a nozzle for a gas-switching device for high- or medium-voltage applications which is highly reliable, relatively easy to realize and at competitive costs.

This aim, these objects and others which will become apparent hereinafter are achieved by a nozzle for a medium or high voltage gas switching device of the type having at least a couple
15 of separable arc contacts, comprising a hollow shaped body suitable to be positioned inside the device around the zone where electric arcs form between said arc contacts during switching operations, characterized in that said hollow shaped body has a first portion electrically conductive and a second portion made of electrically insulating material which surrounds at least partially said first portion.

20 Further characteristics and advantages will become apparent from the description of some preferred but not exclusive embodiments of a nozzle according to the invention, illustrated only by way of non-limitative examples with the accompanying drawing of Figure 1 which is a sectional plan view schematically illustrating the nozzle according to the invention used inside the interruption unit of a circuit breaker.

25 The nozzle according to the invention is particularly suitable for use in medium or high

voltage circuit breakers and will be described by making reference to its use with such a type of switching devices, without intending however to limit in any way its possible applications.

Figure 1 schematically illustrates part of the interruption equipment of a circuit breaker in an open position; as shown, said circuit breaker comprises a puffer chamber 10, a fixed arc contact 1, realized for example by means of a conducting rod, a mobile arcing contact 2, constituted for example by a hollow metallic tube, which is operatively connected to suitable actuation means (not illustrated) devised to displace the mobile arc contact during operations from a first position in which it is electrically coupled to the fixed arc 1, and a second position where it is separated therefrom. The interruption equipment is normally placed inside a casing (not illustrated), made for example of porcelain or other suitable polymeric composite materials, which is filled with insulating gas, e.g. SF₆.

In normal operating conditions, the two arc contacts 1 and 2 are electrically coupled with the head of the fixed contact 1 housed inside the tubular body of the mobile arc contact 2; if opening of the breaker occurs (direction of the mobile equipment along the arrow 3), an electric arc normally strikes at the zone 20 where the two arcing contacts start to separate; a suitable nozzle is positioned around the zone 20 where the arcs strike in order to quench and restrain their effects.

Advantageously, the nozzle according to the invention comprises a hollow shaped body 100, preferably having a substantially cylindrical symmetry, and comprising a first portion 101 electrically conductive, and a second portion 102 which is made of substantially electrically insulating material that surrounds at least partially the first portion 101.

According to a preferred embodiment, the nozzle is constituted by a unique integral body with the first portion 101 incorporated in the second portion 102.

Further, the first portion 101 is advantageously shaped so as to act as an electric shield; in particular, the first portion 101 has preferably a substantially annular shape, for example a

shaped annular body or a shaped ring, placed at an inner circumference of the hollow body, and the second portion 102 surrounds the first portion 101 without fully enclosing it, i.e. it is shaped so as the internal boundary surface 120 of the annular body is not in contact with the second portion but is left uncovered. This allows to have a smooth electrical field distribution between the open arcing contacts and its surroundings, and to optimize the shielding function according to a simple and functionally optimized solution.

The second portion 102 has a lower tip part 103 which has a shaped profile so as to act as a puffer cap, i.e. during opening it acts as a piston and compresses the gas inside the chamber 10, thus allowing flow of the gas through the nozzle itself.

Preferably, the second portion 102 is ~~made of~~ moldable insulating material, such as a thermoplastic resin able to withstand high temperature and pressure conditions; in this way, the second portion 102 of the nozzle body according to the invention can be advantageously manufactured by direct injection molding, that allows to properly shaping the second portion in a relatively easy and cost-effective way.

Proper moldable insulating materials for the second portion 102 are for example fluorine based compounds, preferably a fluorinated co-polymer ethylene-propylene, commercially known as FEP, or perfluoroalkoxy polymers, commercially known as PFA, both produced by DuPont or by Dyneon, or mixtures thereof. Particularly suitable for being used in the second portion 102 are materials of the family of PFA which comprise co-polymer of tetrafluoroethylene and a perfluoropropylvinylether, commercially known as Hyflon PFA, or a perfluoromethylvinylether, commercially known as Hyflon MFA, both produced by Solvay.

In a preferred embodiment, the first portion 101 is also realized by using a moldable conductive material, and comprises an insulating matrix and a filler. The insulating matrix is realized by means of a material selected from those above indicated for the second portion 102, e.g. FEP, PFA, or mixtures thereof; advantageously, both portions 101 and 102 are

realized using the same moldable insulating material.

In turn, the filler is made of one or more electrical conductive materials, for example graphite or carbon or superconductive carbon or mixtures thereof, preferably in form of powder or grains of proper dimensions, chosen in the range from nanometers to millimeters. In order to
5 ensure a proper conductivity and stability of the material, the volume of the filler is chosen in the range between 0,1% and 40%, of the total volume of the first portion, preferably between 0,5% and 35%, more preferably between 1% and 30%.

According to this embodiment, the nozzle is preferably manufactured by co-injection molding of the materials forming the two portions in a unique mold; this allows to manufacture the
10 nozzle according to a process which is extremely simple and at lower cost with respect to known solutions.

Alternatively, the first portion 101 can be made completely of a metallic annular piece; according to this solution, the nozzle is manufactured positioning in a mold the first portion 101 and then injecting the moldable insulating material of the second portion 102 directly
15 thereon.

As previously mentioned, the nozzle according to the invention is suitable for applications with different types of high-or medium voltage gas insulated switching devices, in particular circuit breakers; accordingly, the present invention also relates to a high-or medium voltage gas insulated switching device comprising a nozzle as previously described.

20 As mentioned above, the nozzle is positioned around the arc contacts 1 and 2, i.e. when they are in electrical coupling, in order to delimit the zone 20 where the electric arcs form between them during opening and closing operations; according to a particularly preferred embodiment, shown in figure 1, the nozzle is mechanically secured directly onto the mobile arc contact 2 by means of connecting means 110. In this way, assembly steps are significantly
25 simplified with respect to known solutions; further, this solution is independent from the

presence of the so-called main or permanent contacts, thus resulting in a greater flexibility of applications and reduction of overall production costs.

Preferably, the nozzle is mechanically secured directly onto the mobile arc contact 2 by means of conductive connecting means 110, e.g. metallic screw means or nails or rivets, which are
5 advantageously configured and positioned so as to electrically connect the first portion 101 with the arc contact 2; in this way the conductive part of the nozzle is at the same voltage of the mobile arc contact 2, thus allowing the electric shielding action.

In this way, the connecting means 110 perform at the same time both mechanical and electrical functions, with a consequent further simplification in realizing and assembling the
10 switching device, according to an extremely compact constructive solution.

In practice, it has been found that the nozzle according to the present invention fully achieves the intended aim and objects, giving several advantages with respect to prior art solutions. In fact, as previously described, the nozzle is realized by a unique body which, thanks to its innovative structure, is able to perform several functions which in the prior art are instead performed by
15 several different elements; in particular, the nozzle according to the present invention is able to work at the same time, not only as part an arc quenching element, but also as an electric shield, and also as a puffer cap. Further, it can be realized by means of extremely simplified manufacturing operations, thus obtaining significant savings in terms of material, time and production costs.

20 Finally, its assembling inside a gas-switching device, and connections with the other components of it, are very simple, functionally effective and fast with an optimized internal space occupation. This results in an overall improved switching device.

The nozzle and the related switching device thus conceived, are susceptible of modifications and variations, all of which are within the scope of the inventive concept; all the details may
25 furthermore be replaced with technically equivalent elements. For example the electrically

conductive portion could be completely incorporated inside and fully covered by the second portion 102. In practice, the materials used, so long as they are compatible with the specific use, as well as the dimensions, may be any according to the requirements and the state of the art.

CLAIMS

1. Nozzle for a medium or high voltage gas switching device of the type having at least a couple of separable arc contacts (1, 2), comprising a hollow shaped body (100) suitable to be positioned inside the device around the zone (20) where electric arcs form between said arc contacts (1, 2) during switching operations, characterized in that said hollow shaped body (100) has a first portion (101) electrically conductive and a second portion (102) made of electrically insulating material which surrounds at least partially said first portion (101).
2. Nozzle according to claim 1, characterized in that said hollow shaped body (100) is realized in a single body with said first portion (101) incorporated in said second portion (102).
3. Nozzle according to claim 1, characterized in that said first portion (101) is shaped so as to act as an electric shield.
4. Nozzle according to one or more of the preceding claims, characterised in that said first portion (101) has a substantially annular shape and is positioned along an inner circumference path of the hollow shaped body (100).
5. Nozzle according to one or more of the preceding claims, characterised in that said first portion (101) and /or said second portion (102) comprise moldable materials.
6. Nozzle according to claim 5, characterized in that said first portion (101) is made of a matrix of substantially moldable insulating material and a conductive filler.
7. Nozzle according to claim 6, characterized in that the volume of said filler is in the range between 0,1% and 40%, preferably 0,5% and 35%, more preferably 1% and 30%, of the total volume of said first portion.
8. Nozzle according to one or more of the claims from 1 to 4, characterized in that the said first portion (101) is substantially made of a metallic piece.

9. Nozzle according to one or more of the preceding claims characterized in that it is realized by means of co-injection molding.
10. Gas switching device for high and medium voltage applications comprising at least a mobile arc contact (2) and a fixed arc contact (1), characterized in that it comprises a
5 nozzle according to one or more of the preceding claims.
11. Gas switching device according to claim 10 characterized in that said nozzle is mechanically secured directly onto said mobile arc contact (2).
12. Gas switching device according to claim 11, characterized in that said nozzle is mechanically secured directly to the mobile arc contact (2) by means of conductive
10 connecting means (110) which are configured so as to electrically connect said mobile arc contact (2) to said first portion (101).




FIG. 1

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 H01H33/70

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H01H

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 420 662 A (NIEMEYER LUTZ ET AL) 13 December 1983 (1983-12-13)	1-7,9,10
Y	column 2, line 54 - column 4, line 50; figures 1-3	8,11,12
X	US 4 445 019 A (GAUPP OSVIN ET AL) 24 April 1984 (1984-04-24)	1,5
Y	column 2, line 6 - line 48; figure 1	11
A		2-4, 6-10,12
X	US 3 364 327 A (CROMER CHARLES F) 16 January 1968 (1968-01-16)	1-5
Y	column 3, line 22 - line 35; figure 3	8
A		6,7,9-12
	-/-	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

15 March 2005

Date of mailing of the international search report

24/03/2005

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Drabko, J

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	DE 880 338 C (LICENTIA GMBH) 22 June 1953 (1953-06-22)	1-3
A	page 2, column 1, line 35 - line 73; figure 1	4-12
Y	US 4 707 576 A (SEBALJ RENATA ET AL) 17 November 1987 (1987-11-17) figure 1	12
Y	US 4 418 255 A (HESS RUEDIGER ET AL) 29 November 1983 (1983-11-29) column 2, line 47 - line 59; figure 1	12

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4420662	A	13-12-1983	CH 652528 A5 DE 3044836 A1	15-11-1985 13-05-1982
US 4445019	A	24-04-1984	BR 8206973 A EP 0081253 A1 JP 58103733 A	11-10-1983 15-06-1983 20-06-1983
US 3364327	A	16-01-1968	GB 1114031 A	15-05-1968
DE 880338	C	22-06-1953	CH 302698 A DE 868939 C DE 880337 C FR 1059919 A GB 712785 A	31-10-1954 02-03-1953 22-06-1953 29-03-1954 28-07-1954
US 4707576	A	17-11-1987	CH 667039 A5 CH 667940 A5 DE 3681969 D1 EP 0205897 A2 ES 297069 U JP 2649222 B2 JP 61296610 A DE 3532963 A1	15-09-1988 15-11-1988 21-11-1991 30-12-1986 01-04-1989 03-09-1997 27-12-1986 05-03-1987
US 4418255	A	29-11-1983	DE 3041083 A1 BR 8106987 A DE 8029069 U1 EP 0051556 A1 JP 57107525 A	03-06-1982 13-07-1982 26-05-1988 12-05-1982 05-07-1982